

60,469-054
OT-4986**AMENDMENTS TO THE CLAIMS:**

This listing of claims will replace all prior versions, and listings, of claims in the application:

Listing of Claims:

1. (Previously Presented) A method of making an elevator belt assembly having a plurality of cords within a jacket, comprising the steps of:
 - (a) aligning the plurality of cords in a selected arrangement;
 - (b) applying a selected jacket material to the cords to encase the cords in the jacket with a generally smooth, uninterrupted surface on an exterior of the jacket that is adapted to contact sheaves in an elevator system; and
 - (c) maintaining a selected tension on each of the cords on an individual cord basis while applying the jacket such that the tension on the cords controls positions of the cords within the jacket and the cords are uniformly spaced from the generally smooth, uninterrupted surface on the jacket along the length of the belt assembly.
2. (Original) The method of claim 1, including maintaining different tensions on different ones of the cords.

60,469-054
OT-4986

3. (Original) The method of claim 1, including performing steps (a) through (c) to make a sample belt assembly;
inspecting the sample belt assembly;
determining whether a configuration of the sample belt assembly is consistent with a desired configuration; and
adjusting the tension maintained on at least one of the cords when the determined configuration is not consistent with the desired configuration.
4. (Original) The method of claim 3, including repeating the steps of claim 3 until the sample belt configuration is consistent with the desired configuration.
5. (Original) The method of claim 1, wherein the jacket material comprises a waxless urethane.
6. (Original) The method of claim 5, wherein step (B) includes using a molding device and including cooling at least one of the jacket material or the molding device as the applied jacket and the cords exit the molding device.
7. (Original) The method of claim 6, including applying a fluid to the jacket material or the molding device.

60,469-054
OT-4986

8. (Original) The method of claim 1, including using a molding device and wherein the molding device has an opening through which the belt assembly proceeds, the opening comprising a non-linear configuration such that a thickness of the jacket exiting the opening varies across the width of the jacket.

9. (Original) The method of claim 1, including finishing the exterior of the jacket by forcing the jacket into a shaping device that ensures that the jacket exterior has a desired configuration and cooling the belt assembly.

10 - 13. (Cancelled)

14. (Previously Presented) An elevator belt assembly, comprising:
a plurality of cords aligned generally parallel to a longitudinal axis of the belt along a length of the belt; and
a jacket over the cords, the jacket including a generally smooth, uninterrupted exterior surface extending along the entire belt length that is adapted to contact other components in an elevator system as the belt moves, wherein the jacket comprises a waxless polyurethane.

60,469-054
OT-4986

15. (Previously Presented) An elevator belt assembly made by the process, comprising the steps of:

- (a) aligning a plurality of cords in a selected arrangement;
- (b) applying a selected jacket material to the cords to encase the cords in the jacket with a smooth, uninterrupted surface on an exterior of the jacket that is adapted to contact sheaves in an elevator system; and
- (c) maintaining a selected tension on each of the cords on an individual cord basis while applying the jacket such that the tension on the cords controls positions of the cords within the jacket and the cords are uniformly spaced from the smooth, uninterrupted surface on the jacket along the length of the belt assembly.

16. (Original) The assembly of claim 15, wherein the process includes maintaining different tensions on different ones of the cords.

17. (Original) The assembly of claim 15, wherein the jacket material comprises a waxless urethane and wherein step (b) of the process includes using a molding device and including cooling at least one of the jacket material or the molding device as the applied jacket and the cords exit the molding device.

18. (Original) The assembly of claim 17, wherein the process includes applying a fluid to the jacket material or the molding device.

60,469-054
OT-4986

19. (Original) The assembly of claim 15, wherein the jacket material comprises polyurethane and the cords comprise steel.
20. (Original) The assembly of claim 15, wherein the process includes finishing the exterior of the jacket by forcing the jacket into a shaping device that ensures that the jacket exterior has a desired configuration and cooling the belt assembly.
21. (Previously Presented) A method of making an elevator belt assembly having a plurality of cords within a jacket, comprising the steps of:
- (a) aligning the plurality of cords in a selected arrangement;
 - (b) applying a waxless urethane jacket material to the cords to encase the cords in the jacket with a generally smooth, uninterrupted surface on an exterior of the jacket that is adapted to contact sheaves in an elevator system; and
 - (c) maintaining a selected tension on the cords, respectively, while applying the jacket such that the tension on the cords controls positions of the cords within the jacket and the cords are uniformly spaced from the generally smooth, uninterrupted surface on the jacket along the length of the belt assembly.
22. (Previously Presented) The method of claim 21, wherein step (b) includes using a molding device and including cooling at least one of the jacket material or the molding device as the applied jacket and the cords exit the molding device.

60,469-054
OT-4986

23. (Previously Presented) The method of claim 22, including applying a fluid to the jacket material or the molding device.

24. (Previously Presented) A method of making an elevator belt assembly having a plurality of cords within a jacket, comprising the steps of:

- (a) aligning the plurality of cords in a selected arrangement;
- (b) applying a selected urethane jacket material to the cords to encase the cords in the jacket with a generally smooth, uninterrupted surface on an exterior of the jacket that is adapted to contact sheaves in an elevator system;
- (c) maintaining a selected tension on the cords, respectively, while applying the jacket such that the tension on the cords controls positions of the cords within the jacket and the cords are uniformly spaced from the generally smooth, uninterrupted surface on the jacket along the length of the belt assembly; and
- (d) using a molding device that has an opening through which the belt assembly proceeds, the opening comprising a non-linear configuration such that a thickness of the jacket exiting the opening varies across the width of the jacket.

25. (Cancelled)

60,469-054
OT-4986

26. (Previously Presented) An elevator belt assembly made by the process, comprising the steps of:

- (a) aligning a plurality of cords in a selected arrangement;
- (b) applying a waxless urethane jacket material to the cords using a molding device and cooling at least one of the jacket material or the molding device as the applied jacket and the cords exit the molding device to encase the cords in the jacket with a smooth, uninterrupted surface on an exterior of the jacket that is adapted to contact sheaves in an elevator system; and
- (c) maintaining a selected tension on the cords, respectively, while applying the jacket such that the tension on the cords controls positions of the cords within the jacket and the cords are uniformly spaced from the smooth, uninterrupted surface on the jacket along the length of the belt assembly.

27. (Previously Presented) The assembly of claim 26, wherein the process includes applying a fluid to the jacket material or the molding device.

28. (Previously Presented) The method of claim 1, including moving the cords in a direction parallel to a length of the cords while applying the jacket material to the cords.

29. (Previously Presented) The method of claim 1, including adjusting the tension on at least one of the cords while applying the jacket material to the cords.

60,469-054
OT-4986

30. (Previously Presented) The method of claim 1, including maintaining the selected tension on each of the cords such that the selected tension is the same on opposite sides of a jacket application station used for applying the jacket material to the cords for each individual cord.

31. (Previously Presented) The method of claim 1, including applying the jacket material to the cords in a continuous and uninterrupted manner from near a first end of the cords to near a second, opposite end of the cords.

32 (Previously Presented) The assembly of claim 15, wherein the processing includes moving the cords in a direction parallel to a length of the cords while applying the jacket material to the cords.

33 (Previously Presented) The assembly of claim 15, wherein the processing includes adjusting the tension on at least one of the cords while applying the jacket material to the cords.

34 (Previously Presented) The assembly of claim 15, wherein the processing includes maintaining the selected tension on each of the cords such that the selected tension is the same on opposite sides of a jacket application station used for applying the jacket material to the cords for each individual cord.

60,469-054
OT-4986

35. (Previously Presented) The assembly of claim 5, wherein the process includes applying the jacket material to the cords in a continuous and uninterrupted manner from near a first end of the cords to near a second, opposite end of the cords.
36. (Previously Presented) The method of claim 24, including moving the cords in a direction parallel to a length of the cords while applying the jacket material to the cords.
37. (Previously Presented) The method of claim 24, including adjusting the tension on at least one of the cords while applying the jacket material to the cords.
38. (Previously Presented) The method of claim 24, including maintaining the selected tension on each of the cords such that the selected tension is the same on opposite sides of a jacket application station used for applying the jacket material to the cords for each individual cord.
39. (Previously Presented) The method of claim 24, including applying the jacket material to the cords in a continuous and uninterrupted manner from near a first end of the cords to near a second, opposite end of the cords.
40. (New) The method of claim 1, comprising
providing a plurality of cords that are all of the same construction.

60,469-054
OT-4986

41. (New) The elevator belt assembly of claim 14, wherein the plurality of cords are all of the same construction.

42. (New) The elevator belt assembly of claim 15, wherein the entire plurality of cords are all of the same construction.

**This Page is Inserted by IFW Indexing and Scanning
Operations and is not part of the Official Record**

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:

- ☐ BLACK BORDERS
- ☐ IMAGE CUT OFF AT TOP, BOTTOM OR SIDES
- ☐ FADED TEXT OR DRAWING
- ☐ BLURRED OR ILLEGIBLE TEXT OR DRAWING
- ☐ SKEWED/SLANTED IMAGES
- ☐ COLOR OR BLACK AND WHITE PHOTOGRAPHS
- ☐ GRAY SCALE DOCUMENTS
- ☒ LINES OR MARKS ON ORIGINAL DOCUMENT
- ☐ REFERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY
- ☐ OTHER: _____

IMAGES ARE BEST AVAILABLE COPY.

As rescanning these documents will not correct the image problems checked, please do not report these problems to the IFW Image Problem Mailbox.